

PRISMACOM WATT (50 Hz) R407A

Condiciones de Cálculo: Gas de aspiración 25°C, sin subenfriamiento de líquido.
 Condizioni di calcolo: Gas di aspirazione 25°C senza sottoraffreddamento del liquido
 Conditions de Calcul: Gaz aspirés 25°C, sans sous-refroidissement du liquide
 Kälteleistung: 25°C Sauggasttemperatur ohne Flüssigkeitsunterkühlung
 Rating conditions: Suction return gas 25°C, without liquid subcooling.



COMPRESOR / COMPRESSOR	TEMP. CONDENSACION / CONDENSING TEMP. (°C)		TEMPERATURA DE EVAPORACION / EVAPORATING TEMPERATURE (°C)												
			H = Alta / High					M = Media / Medium			L = Baja / Low				
			12,5	10	7	5	0	-5	-10	-15	-20	-25	-30	-35	-40
07K3.2X	Pf	30	2597					2112	1692	1339	1030	780	567	390	246
		40	2251					1810	1435	1118	853	625	441	287	162
		50	1891					1508	1177	905	670	475	316	188	85
	Pa	30	574					552	515	471	427	375	316	265	213
		40	670					625	567	508	449	383	309	250	184
		50	743					677	603	530	449	368	287	213	140
07K5.2X	Pf	30									1837	1409	1040	738	496
		40									1545	1156	841	578	364
		50									1253	913	641	418	243
	Pa	30									748	670	583	486	408
		40									807	700	583	476	379
		50									836	700	573	447	330
1K5.2X	Pf	30	4486					3655	2949	2340	1827	1402	1035	735	493
		40	3906					3162	2533	1992	1537	1151	836	575	363
		50	3326					2669	2117	1644	1247	909	638	416	242
	Pa	30	1021					981	922	852	763	684	595	496	416
		40	1199					1120	1031	932	823	714	595	486	387
		50	1358					1239	1120	981	852	714	585	456	337
1K7.2X	Pf	30									2473	1903	1425	1028	702
		40									2086	1588	1170	819	539
		50									1720	1282	916	621	387
	Pa	30									987	875	763	641	539
		40									1069	926	784	641	509
		50									1120	957	784	621	468
1,5K7.2X	Pf	30	5935					4851	3919	3129	2461	1894	1418	1023	699
		40	5195					4223	3393	2684	2076	1580	1165	815	537
		50	4436					3585	2856	2228	1712	1276	911	618	385
	Pa	30	1287					1227	1157	1068	968	858	748	629	529
		40	1527					1427	1307	1187	1048	908	768	629	499
		50	1736					1597	1437	1267	1098	938	768	609	459
1,5K8.2X	Pf	30									2888	2232	1676	1222	843
		40									2454	1868	1383	990	661
		50									2030	1525	1101	762	490
	Pa	30									1151	1020	899	767	646
		40									1242	1091	929	778	626
		50									1323	1131	939	757	586
1.5K9.2X	Pf	30									3541	2739	2064	1506	1047
		40									3023	2308	1712	1223	831
		50									2504	1888	1379	959	626
	Pa	30									1399	1242	1076	919	773
		40									1526	1321	1125	939	753
		50									1624	1379	1144	919	714
2K8.2X	Pf	30	6903					5647	4572	3657	2874	2221	1668	1216	839
		40	6049					4923	3959	3135	2442	1859	1377	985	658
		50	5185					4190	3346	2633	2020	1517	1095	759	487
	Pa	30	1475					1416	1337	1238	1129	1000	881	752	634
		40	1762					1643	1515	1376	1218	1069	911	762	614
		50	2010					1841	1663	1475	1297	1109	921	743	574
2K9.2X	Pf	30	6901					5596	4477	3523	2725	2054	1499	1041	
		40	6025					4847	3845	3007	2297	1703	1217	827	
		50	5139					4107	3231	2492	1878	1372	954	623	
	Pa	30	1745					1640	1515	1371	1218	1055	901	758	
		40	2052					1880	1688	1496	1295	1103	921	738	
		50	2330					2081	1841	1592	1352	1122	901	700	
2L9.2X	Pf	30	8240					6711	5403	4292	3343	2550	1888	1341	899
		40	7161					5796	4627	3630	2796	2093	1512	1038	662
		50	6082					4872	3850	2984	2256	1651	1153	756	437
	Pa	30	1741					1668	1561	1431	1283	1128	965	801	646
		40	2076					1929	1758	1570	1373	1177	973	777	597
		50	2346					2134	1905	1668	1422	1177	948	719	515
2L13.2X	Pf	30									4858	3720	2770	1989	1356
		40									4086	3087	2256	1573	1029
		50									3324	2464	1751	1177	722
	Pa	30									1890	1662	1425	1187	970
		40									2038	1741	1454	1177	920
		50									2127	1781	1435	1118	821
3L13.2X	Pf	30	11679					9519	7679	6112	4779	3660	2725	1956	1333
		40	10171					8244	6599	5197	4020	3037	2219	1548	1012
		50	8662					6969	5519	4302	3270	2423	1723	1158	711
	Pa	30	2474					2369	2215	2033	1832	1611	1381	1151	940
		40	2963					2752	2513	2254	1975	1688	1410	1141	892
		50	3366					3069	2743	2407	2062	1726	1391	1084	796
3L17.2X	Pf	30	13102					10590	8461	6649	5121	3854	2806	1954	
		40	11387					9149	7250	5645	4302	3188	2282	1539	
		50	9684					7719	6059	4662	3505	2544	1769	1157	
	Pa	30	3275					3079	2839	2555	2271	1965	1660	1376	
		40	3821					3505	3155	2784	2413	2042	1681	1354	
		50	4280					3854	3406	2948	2500	2064	1660	1288	
3L19.2X	Pf	30									7084	5393	3979	2829	1890
		40									5891	4399	3172	2177	1381
		50									4719	3448	2409	1569	912
	Pa	30									2719	2387	2034	1691	1359
		40									2896	2465	2045	1636	1260
		50									2973	2465	1967	1503	1083
4L17.2X	Pf	30	15959					13036	10538	8419	6616	5095	3835	2792	1945
		40	13938					11331	9104	7213	5617	4280	3172	2271	1532
		50	11928					9636	7681	6029	4639	3487	2531	1760	1152
	Pa	30	3340					3211	3019	2783	2505	2226	1927	1627	1349
		40	4014					3746	3436	3093	2730	2366	2002	1648	1327
		50	4592					4196	3778	3340	2890	2451	2023	1627	1263

PRISMACOM

WATT (50 Hz) R407A

Condiciones de Cálculo: Gas de aspiración 25°C, sin subenfriamiento de líquido.
 Condizioni di calcolo: Gas di aspirazione 25°C senza sottoraffreddamento del liquido
 Conditions de Calcul: Gaz aspire 25°C, sans sous-refroidissement du liquide
 Kälteleistung: 25°C Sauggasttemperatur ohne Flüssigkeitsunterkühlung
 Rating conditions: Suction return gas 25°C, without liquid subcooling.



COMPRESOR / COMPRESSOR	TEMP. CONDENSACION / CONDENSING TEMP. (°C)		TEMPERATURA DE EVAPORACION / EVAPORATING TEMPERATURE (°C)												
			H = Alta / High					M = Media / Medium			L = Baja / Low				
			12,5	10	7	5	0	-5	-10	-15	-20	-25	-30	-35	-40
4L19.2X	Pf	30						14241	11437	9061	7049	5366	3959	2815	1880
		40						12251	9754	7632	5861	4377	3156	2166	1375
		50						10260	8072	6235	4696	3431	2397	1562	907
	Pa	30						3478	3251	2980	2665	2340	1994	1658	1333
		40						3998	3641	3251	2839	2416	2005	1604	1235
		50						4399	3922	3424	2915	2416	1929	1474	1062
4L23.2X	Pf	30									8369	6386	4741	3392	2299
		40									6989	5252	3822	2657	1727
		50									5661	4169	2943	1972	1196
	Pa	30									3178	2769	2360	1952	1574
		40									3413	2902	2391	1911	1471
		50									3536	2922	2340	1788	1298
5L23.2X	Pf	30	20538					16705	13441	10666	8327	6355	4718	3376	2288
		40	17813					14407	11489	9029	6955	5226	3803	2644	1718
		50	15109					12109	9568	7422	5633	4148	2928	1962	1190
	Pa	30	4258					4067	3807	3476	3116	2715	2314	1913	1543
		40	5079					4718	4298	3837	3346	2845	2344	1873	1443
		50	5760					5229	4658	4067	3466	2865	2294	1753	1272
3LR13.2X	Pf	30	11973					9758	7872	6266	4899	3751	2794	2005	1367
		40	10426					8451	6765	5328	4121	3113	2275	1586	1038
		50	8880					7144	5657	4410	3352	2484	1766	1187	728
	Pa	30	2625					2513	2350	2157	1943	1709	1465	1221	997
		40	3143					2920	2665	2391	2096	1790	1495	1211	946
		50	3571					3255	2909	2553	2187	1831	1475	1150	844
3LR17.2X	Pf	30						13102	10590	8461	6649	5121	3854	2806	1954
		40						11387	9149	7250	5645	4302	3188	2282	1539
		50						9684	7719	6059	4662	3505	2544	1769	1157
	Pa	30						3275	3079	2839	2555	2271	1965	1660	1376
		40						3821	3505	3155	2784	2413	2042	1681	1354
		50						4280	3854	3406	2948	2500	2064	1660	1288
4LR17.2X	Pf	30	15959					13036	10538	8419	6616	5095	3835	2792	1945
		40	13938					11331	9104	7213	5617	4280	3172	2271	1532
		50	11928					9636	7681	6029	4639	3487	2531	1760	1152
	Pa	30	3340					3211	3019	2783	2505	2226	1927	1627	1349
		40	4014					3746	3436	3093	2730	2366	2002	1648	1327
		50	4592					4196	3778	3340	2890	2451	2023	1627	1263
4LR23.2X	Pf	30									8369	6386	4741	3392	2299
		40									6989	5252	3822	2657	1727
		50									5661	4169	2943	1972	1196
	Pa	30									3178	2769	2360	1952	1574
		40									3413	2902	2391	1911	1471
		50									3536	2922	2340	1788	1298
5LR23.2X	Pf	30	20538					16705	13441	10666	8327	6355	4718	3376	2288
		40	17813					14407	11489	9029	6955	5226	3803	2644	1718
		50	15109					12109	9568	7422	5633	4148	2928	1962	1190
	Pa	30	4258					4067	3807	3476	3116	2715	2314	1913	1543
		40	5079					4718	4298	3837	3346	2845	2344	1873	1443
		50	5760					5229	4658	4067	3466	2865	2294	1753	1272
6MR27.2X	Pf	30									10054	7710	5764	4157	2857
		40									8457	6399	4689	3307	2191
		50									6911	5130	3686	2508	1587
	Pa	30									3819	3358	2887	2416	1976
		40									4126	3532	2959	2406	1894
		50									4300	3604	2938	2314	1751
7MR27.2X	Pf	30	24450					19947	16076	12785	10004	7671	5736	4136	2842
		40	21292					17248	13794	10870	8415	6367	4666	3291	2180
		50	18114					14568	11553	9006	6877	5104	3668	2496	1579
	Pa	30	5049					4838	4537	4166	3744	3292	2831	2369	1937
		40	6023					5611	5129	4597	4045	3463	2901	2359	1857
		50	6836					6233	5591	4908	4216	3533	2881	2269	1716
7MR32.2X	Pf	30									12348	9519	7178	5241	3670
		40									10472	7989	5941	4268	2920
		50									8668	6529	4765	3345	2220
	Pa	30									4663	4126	3579	3041	2524
		40									5069	4390	3721	3082	2494
		50									5363	4552	3781	3051	2403
9MR32.2X	Pf	30	28889					23583	19073	15221	11968	9227	6957	5080	3557
		40	25253					20488	16459	13030	10150	7743	5758	4137	2830
		50	21569					17422	13884	10897	8401	6328	4618	3243	2152
	Pa	30	5906					5673	5335	4918	4454	3940	3418	2905	2411
		40	7068					6603	6070	5470	4841	4192	3553	2943	2382
		50	8055					7377	6651	5896	5122	4347	3611	2914	2295
6GR31.3X	Pf	30									11994	9246	6972	5091	3565
		40									10172	7759	5770	4146	2836
		50									8419	6341	4628	3250	2157
	Pa	30									4530	4008	3476	2954	2452
		40									4924	4264	3614	2993	2422
		50									5209	4421	3673	2964	2334
8GR31.3X	Pf	30	28950					23633	19113	15253	11994	9246	6972	5091	3565
		40	25307					20531	16494	13057	10172	7759	5770	4146	2836
		50	21614					17459	13914	10920	8419	6341	4628	3250	2157
	Pa	30	6007					5770	5426	5002	4530	4008	3476	2954	2452
		40	7188					6716	6174	5564	4924	4264	3614	2993	2422
		50	8193					7503	6765	5997	5209	4421	3673	2964	2334
8GR39.3X	Pf	30									14896	11408	8493	6093	
		40									12545	9474	6938	4849	
		50									10251	7618	5442		
	Pa	30									5451	4790	4110	3430	
		40									5879	5043	4198	3391	
		50									6151	5150	4169		

PRISMACOM

WATT (50 Hz) R407A

Condiciones de Cálculo: Gas de aspiración 25°C, sin subenfriamiento de líquido.
 Condizioni di calcolo: Gas di aspirazione 25°C senza sottoraffreddamento del liquido
 Conditions de Calcul: Gaz aspire 25°C, sans sous-refroidissement du liquide
 Kälteleistung: 25°C Sauggasttemperatur ohne flüssigkeitsunterkühlung
 Rating conditions: Suction return gas 25°C, without liquid subcooling.



COMPRESOR / COMPRESSOR	TEMP. CONDENSACION / CONDENSING TEMP. (°C)		TEMPERATURA DE EVAPORACION / EVAPORATING TEMPERATURE (°C)												
			H = Alta / High					M = Media / Medium			L = Baja / Low				
			12,5	10	7	5	0	-5	-10	-15	-20	-25	-30	-35	-40
10GR39.3X	Pf	30	36209					29538	23785	18941	14822	11351	8450	6062	
		40	31520					25525	20449	16137	12482	9427	6903	4825	
		50	26782					21561	17123	13362	10200	7580	5414		
	Pa	30	7380					7050	6604	6061	5440	4781	4102	3423	
		40	8776					8165	7467	6691	5867	5033	4189	3384	
		50	9959					9087	8136	7157	6139	5140	4160		
10GR50.3X	Pf	30									18407	13961	10259	7204	
		40									15288	11383	8158	5517	
		50									12243	8890	6153		
	Pa	30									6631	5782	4912	4031	
		40									7044	5962	4891	3840	
		50									7214	5930	4668		
15GR50.3X	Pf	30	45603					37105	29769	23593	18315	13892	10208	7168	
		40	39480					31880	25388	19856	15212	11327	8118	5489	
		50	33252					26602	20975	16193	12182	8846	6123		
	Pa	30	9127					8693	8110	7411	6617	5770	4902	4023	
		40	10757					9974	9074	8079	7030	5950	4881	3833	
		50	12070					10958	9751	8491	7200	5919	4659		
12GR60.3X	Pf	30									22791	17353	12726	8833	
		40									19094	14291	10261	6906	
		50									15553	11415	7992		
	Pa	30									8256	7238	6211	5174	
		40									8862	7600	6338	5096	
		50									9224	7727	6250		
18GR60.3X	Pf	30	55380					45258	36596	29101	22678	17266	12663	8789	
		40	48129					39078	31291	24673	18999	14220	10210	6871	
		50	40878					32946	26182	20390	15475	11358	7952		
	Pa	30	11441					10826	10065	9196	8239	7224	6199	5164	
		40	13286					12320	11246	10074	8844	7585	6326	5086	
		50	14790					13520	12144	10689	9206	7712	6238		

COMPRESORES 4 CILINDROS EN V / 4 CYLINDERS IN V COMPRESSORS

5VLR26.4X	Pf	30						15583	12394	9698	7436	5660	4009	2755		
		40						13371	10537	8157	6172	4523	3190	2113		
		50						11199	8730	6666	4948	3555	2419	1531		
	Pa	30						4464	4098	3684	3239	2785	2331	1906		
		40						5046	4523	3980	3407	2854	2321	1827		
		50						5501	4829	4148	3476	2834	2232	1689		
7VLR26.4X	Pf	30	23583					19240	15506	12332	9649	7399	5532	3989		
		40	20537					16636	13305	10485	8116	6141	4500	3174		
		50	17471					14052	11143	8686	6633	4923	3537	2407		
	Pa	30	4870					4667	4376	4018	3611	3176	2730	2285		
		40	5809					5412	4947	4434	3902	3340	2798	2275		
		50	6593					6012	5393	4734	4066	3408	2779	2188		
5VLR29.4X	Pf	30						17850	14245	11201	8635	6511	4755	3329		
		40						15404	12194	9500	7247	5389	3872	2649		
		50						12995	10199	7863	5923	4322	3035	2014		
	Pa	30						5067	4672	4230	3743	3246	2759	2290		
		40						5766	5196	4598	3982	3375	2796	2262		
		50						6318	5601	4865	4129	3430	2768	2180		
7VLR29.4X	Pf	30	26903					21962	17761	14174	11146	8592	6479	4731	3313	
		40	23517					19079	15327	12134	9453	7211	5362	3852	2635	
		50	20086					16224	12930	10148	7824	5893	4301	3020	2004	
	Pa	30	5599					5378	5057	4662	4222	3735	3240	2753	2285	
		40	6700					6259	5755	5186	4589	3974	3368	2790	2258	
		50	7636					6994	6305	5589	4855	4121	3423	2763	2175	
7VLR33.4X	Pf	30						24624	19778	15656	12160	9223	6775	4758		
		40						21148	16850	13188	10104	7519	5385	3642		
		50						17682	13932	10750	8087	5875	4063			
	Pa	30						5845	5454	4984	4445	3877	3280	2692		
		40						6717	6110	5434	4719	3995	3270	2575		
		50						7392	6570	5718	4837	3965	3123			
10VLR33.4X	Pf	30	30152					24502	19679	15578	12100	9177	6742	4735		
		40	26109					21043	16766	13123	10054	7482	5358	3624		
		50	21969					17594	13863	10697	8047	5845	4043			
	Pa	30	6127					5833	5443	4974	4436	3869	3273	2687		
		40	7241					6703	6097	5423	4710	3987	3264	2570		
		50	8149					7377	6557	5706	4827	3957	3117			
7VLR38.4X	Pf	30						23439	18666	14607	11186	8328	5974			
		40						20152	15903	12301	9290	6803	4755			
		50						16874	13168	10052	7470	5336				
	Pa	30						6489	5955	5345	4697	4030	3363			
		40						7337	6574	5765	4945	4116	3325			
		50						7994	7032	6031	5050	4088				
10VLR38.4X	Pf	30	35506					28964	23323	18573	14534	11130	8286	5944		
		40	30907					25029	20052	15823	12240	9244	6769	4731		
		50	26262					21142	16791	13102	10002	7433	5309			
	Pa	30	7236					6913	6476	5943	5335	4688	4022	3357		
		40	8606					8007	7322	6561	5753	4935	4108	3319		
		50	9766					8910	7978	7018	6019	5040	4079			

PRISMACOM

WATT (50 Hz) R407A

Condiciones de Cálculo: Gas de aspiración 25°C, sin subenfriamiento de líquido.
 Condizioni di calcolo: Gas di aspirazione 25°C senza sottoraffreddamento del liquido
 Conditions de Calcul: Gaz aspirés 25°C, sans sous-refroidissement du liquide
 Kälteleistung: 25°C Sauggasttemperatur ohne flüssigkeitsunterkühlung
 Rating conditions: Suction return gas 25°C, without liquid subcooling.



COMPRESOR / COMPRESSOR	TEMP. CONDENSACION / CONDENSING TEMP. (°C)		TEMPERATURA DE EVAPORACION / EVAPORATING TEMPERATURE (°C)											
			H = Alta / High					M = Media / Medium			L = Baja / Low			
			12,5	10	7	5	0	-5	-10	-15	-20	-25	-30	-35
15VR73.4X	Pf	30					14241	11437	9061	7049	5366	3959	2815	1880
		40					12251	9754	7632	5861	4377	3156	2166	1375
		50					10260	8072	6235	4696	3431	2397	1562	907
	Pa	30					3478	3251	2980	2665	2340	1994	1658	1333
		40					3998	3641	3251	2839	2416	2005	1604	1235
		50					4399	3922	3424	2915	2416	1929	1474	1062
25VR73.4X	Pf	30								8369	6386	4741	3392	2299
		40								6989	5252	3822	2657	1727
		50								5661	4169	2943	1972	1196
	Pa	30								3178	2769	2360	1952	1574
		40								3413	2902	2391	1911	1471
		50								3536	2922	2340	1788	1298
20VR83.4X	Pf	30			20538	16705	13441	10666	8327	6355	4718	3376	2288	
		40			17813	14407	11489	9029	6955	5226	3803	2644	1718	
		50			15109	12109	9568	7422	5633	4148	2928	1962	1190	
	Pa	30			4258	4067	3807	3476	3116	2715	2314	1913	1543	
		40			5079	4718	4298	3837	3346	2845	2344	1873	1443	
		50			5760	5229	4658	4067	3466	2865	2294	1753	1272	
30VR83.4X	Pf	30			11973	9758	7872	6266	4899	3751	2794	2005	1367	
		40			10426	8451	6765	5328	4121	3113	2275	1586	1038	
		50			8880	7144	5657	4410	3352	2484	1766	1187	728	
	Pa	30			2625	2513	2350	2157	1943	1709	1465	1221	997	
		40			3143	2920	2665	2391	2096	1790	1495	1211	946	
		50			3571	3255	2909	2553	2187	1831	1475	1150	844	
25VR93.4X	Pf	30				13102	10590	8461	6649	5121	3854	2806	1954	
		40				11387	9149	7250	5645	4302	3188	2282	1539	
		50				9684	7719	6059	4662	3505	2544	1769	1157	
	Pa	30				3275	3079	2839	2555	2271	1965	1660	1376	
		40				3821	3505	3155	2784	2413	2042	1681	1354	
		50				4280	3854	3406	2948	2500	2064	1660	1288	
35VR93.4X	Pf	30			15959	13036	10538	8419	6616	5095	3835	2792	1945	
		40			13938	11331	9104	7213	5617	4280	3172	2271	1532	
		50			11928	9636	7681	6029	4639	3487	2531	1760	1152	
	Pa	30			3340	3211	3019	2783	2505	2226	1927	1627	1349	
		40			4014	3746	3436	3093	2730	2366	2002	1648	1327	
		50			4592	4196	3778	3340	2890	2451	2023	1627	1263	
30VR118.4X	Pf	30							8369	6386	4741	3392	2299	
		40							6989	5252	3822	2657	1727	
		50							5661	4169	2943	1972	1196	
	Pa	30							3178	2769	2360	1952	1574	
		40							3413	2902	2391	1911	1471	
		50							3536	2922	2340	1788	1298	
40VR118.4X	Pf	30			20538	16705	13441	10666	8327	6355	4718	3376	2288	
		40			17813	14407	11489	9029	6955	5226	3803	2644	1718	
		50			15109	12109	9568	7422	5633	4148	2928	1962	1190	
	Pa	30			4258	4067	3807	3476	3116	2715	2314	1913	1543	
		40			5079	4718	4298	3837	3346	2845	2344	1873	1443	
		50			5760	5229	4658	4067	3466	2865	2294	1753	1272	

PRISMACOM WATT (50 Hz) R407F

Condiciones de Cálculo: Gas de aspiración 25°C, sin subenfriamiento de líquido.
 Condizioni di calcolo: Gas di aspirazione 25°C senza sottoraffreddamento del liquido
 Conditions de Calcul: Gaz aspirés 25°C, sans sous-refroidissement du liquide
 Kälteleistung: 25°C Sauggasttemperatur ohne Flüssigkeitsunterkühlung
 Rating conditions: Suction return gas 25°C, without liquid subcooling.



COMPRESOR / COMPRESSOR	TEMP. CONDENSACION / CONDENSING TEMP. (°C)		TEMPERATURA DE EVAPORACION / EVAPORATING TEMPERATURE (°C)												
			H = Alta / High					M = Media / Medium			L = Baja / Low				
			12,5	10	7	5	0	-5	-10	-15	-20	-25	-30	-35	-40
07K3.2X	Pf	30	2744					2229	1788	1413	1096	831	607	419	272
		40	2391					1928	1530	1199	912	673	475	313	184
		50	2038					1626	1273	979	725	519	346	210	99
	Pa	30	603					581	544	500	449	397	338	280	221
		40	706					662	603	537	471	405	331	265	199
		50	795					721	647	567	478	397	309	228	155
07K5.2X	Pf	30									1953	1496	1108	797	534
		40									1652	1244	904	622	398
		50									1351	991	700	457	267
	Pa	30									797	700	612	515	428
		40									855	738	622	505	398
		50									884	748	612	476	350
1K5.2X	Pf	30	4728					3858	3113	2485	1943	1489	1102	793	532
		40	4148					3365	2698	2127	1644	1238	899	619	396
		50	3568					2872	2272	1769	1344	986	696	454	266
	Pa	30	1070					1031	971	892	813	714	624	525	436
		40	1279					1189	1090	981	872	753	634	515	406
		50	1437					1318	1189	1051	902	763	624	486	357
1K7.2X	Pf	30									2616	2015	1517	1099	753
		40									2229	1700	1252	885	585
		50									1852	1384	992	677	422
	Pa	30									1048	926	804	682	560
		40									1140	987	835	682	550
		50									1201	1018	835	662	499
1,5K7.2X	Pf	30	6259					5124	4142	3312	2603	2005	1509	1094	749
		40	5509					4486	3605	2856	2218	1691	1246	881	582
		50	4760					3848	3069	2400	1843	1377	987	673	420
	Pa	30	1357					1297	1227	1128	1028	908	788	669	549
		40	1616					1517	1397	1257	1118	968	818	669	539
		50	1856					1696	1527	1357	1177	998	818	649	489
1,5K8.2X	Pf	30									3060	2363	1787	1303	909
		40									2625	1999	1484	1060	717
		50									2191	1646	1192	828	530
	Pa	30									1212	1080	949	808	677
		40									1323	1151	990	818	666
		50									1404	1202	1000	808	626
1.5K9.2X	Pf	30									3746	2905	2191	1604	1125
		40									3218	2465	1839	1321	895
		50									2700	2035	1487	1037	680
	Pa	30									1477	1311	1144	968	812
		40									1624	1409	1193	988	802
		50									1731	1467	1223	978	763
2K8.2X	Pf	30	7275					5958	4833	3868	3044	2351	1778	1296	904
		40	6421					5235	4210	3346	2612	1989	1477	1055	713
		50	5556					4501	3597	2823	2180	1638	1186	824	528
	Pa	30	1554					1495	1406	1307	1188	1059	931	792	663
		40	1871					1742	1604	1455	1297	1129	970	802	653
		50	2148					1960	1772	1574	1376	1178	980	792	614
2K9.2X	Pf	30	7280					5908	4730	3728	3044	2351	1778	1296	904
		40	6404					5158	4098	3202	2453	1830	1314	891	
		50	5509					4409	3475	2686	2024	1479	1032	676	
	Pa	30	1851					1736	1601	1448	1285	1122	949	796	
		40	2186					2004	1803	1592	1381	1170	969	786	
		50	2503					2234	1966	1697	1438	1199	959	748	
2L9.2X	Pf	30	8673					7079	5706	4537	3548	2714	2019	1439	973
		40	7602					6164	4929	3883	3000	2256	1635	1128	719
		50	6523					5248	4153	3229	2444	1798	1259	826	474
	Pa	30	1839					1766	1651	1512	1357	1193	1022	850	687
		40	2207					2044	1872	1668	1463	1251	1038	834	638
		50	2510					2273	2035	1782	1520	1267	1014	768	548
2L13.2X	Pf	30									5155	3958	2958	2137	1464
		40									4373	3315	2424	1702	1118
		50									3602	2671	1900	1276	782
	Pa	30									1999	1761	1514	1266	1029
		40									2167	1860	1553	1257	980
		50									2276	1900	1544	1197	871
3L13.2X	Pf	30	12293					10044	8108	6463	5071	3893	2910	2102	1440
		40	10794					8769	7027	5548	4302	3261	2385	1674	1100
		50	9285					7485	5947	4643	3543	2628	1869	1256	769
	Pa	30	2618					2503	2349	2158	1937	1707	1467	1227	997
		40	3145					2925	2676	2397	2100	1803	1506	1218	949
		50	3596					3270	2925	2570	2206	1841	1496	1160	844
3L17.2X	Pf	30						13811	11191	8942	7042	5437	4105	3002	2096
		40						12108	9739	7730	6027	4596	3417	2446	1660
		50						10394	8298	6518	5022	3778	2751	1922	1256
	Pa	30						3461	3254	3002	2708	2402	2074	1758	1463
		40						4061	3723	3352	2959	2566	2173	1791	1441
		50						4575	4105	3625	3144	2664	2205	1758	1365
3L19.2X	Pf	30									7515	5736	4244	3028	2034
		40									6300	4719	3415	2354	1503
		50									5106	3736	2619	1724	1017
	Pa	30									2885	2531	2155	1790	1448
		40									3083	2630	2177	1746	1337
		50									3183	2630	2111	1614	1160
4L17.2X	Pf	30	16795					13743	11135	8897	7007	5410	4085	2988	2086
		40	14796					12048	9690	7691	5997	4574	3400	2433	1651
		50	12787					10342	8256	6486	4997	3759	2738	1912	1249
	Pa	30	3532					3393	3190	2944	2655	2355	2034	1723	1434
		40	4260					3982	3650	3286	2901	2515	2130	1755	1413
		50	4902					4485	4025	3554	3083	2612	2162	1723	1338

PRISMACOM

WATT (50 Hz) R407F

Condiciones de Cálculo: Gas de aspiración 25°C, sin subenfriamiento de líquido.
 Condizioni di calcolo: Gas di aspirazione 25°C senza sottoraffreddamento del liquido
 Conditions de Calcul: Gaz aspire 25°C, sans sous-refroidissement du liquide
 Kälteleistung: 25°C Sauggasttemperatur ohne Flüssigkeitsunterkühlung
 Rating conditions: Suction return gas 25°C, without liquid subcooling.



COMPRESOR / COMPRESSOR	TEMP. CONDENSACION / CONDENSING TEMP. (°C)		TEMPERATURA DE EVAPORACION / EVAPORATING TEMPERATURE (°C)												
			H = Alta / High					M = Media / Medium			L = Baja / Low				
			12,5	10	7	5	0	-5	-10	-15	-20	-25	-30	-35	-40
4L19.2X	Pf	30					15033	12097	9589	7478	5707	4223	3013	2023	
		40					13031	10392	8149	6268	4696	3398	2342	1496	
		50					11041	8699	6730	5081	3717	2606	1716	1012	
	Pa	30					3673	3435	3153	2828	2481	2113	1755	1419	
		40					4247	3868	3456	3023	2579	2135	1712	1311	
		50					4692	4182	3651	3121	2579	2070	1582	1138	
4L23.2X	Pf	30								8869	6785	5058	3627	2473	
		40								7470	5630	4108	2871	1870	
		50								6111	4506	3198	2146	1318	
	Pa	30									3372	2943	2514	2085	1676
		40									3638	3096	2555	2044	1574
		50									3781	3137	2514	1931	1400
5L23.2X	Pf	30				21657	17630	14204	11296	8825	6751	5033	3609	2461	
		40				18942	15322	12242	9629	7432	5602	4087	2857	1861	
		50				16227	13024	10300	8002	6080	4484	3182	2135	1312	
	Pa	30				4508	4308	4027	3687	3306	2885	2464	2044	1643	
		40				5410	5019	4578	4087	3566	3035	2504	2004	1543	
		50				6161	5590	4979	4348	3707	3075	2464	1893	1372	
3LR13.2X	Pf	30				12601	10296	8311	6625	5198	3991	2983	2155	1477	
		40				11065	8989	7204	5687	4410	3342	2444	1716	1127	
		50				9518	7672	6096	4759	3632	2694	1916	1287	788	
	Pa	30				2777	2655	2492	2289	2055	1811	1556	1302	1058	
		40				3337	3103	2838	2543	2228	1912	1597	1292	1007	
		50				3815	3469	3103	2726	2340	1953	1587	1231	895	
3LR17.2X	Pf	30					13811	11191	8942	7042	5437	4105	3002	2096	
		40					12108	9739	7730	6027	4596	3417	2446	1660	
		50					10394	8298	6518	5022	3778	2751	1922	1256	
	Pa	30					3461	3254	3002	2708	2402	2074	1758	1463	
		40					4061	3723	3352	2959	2566	2173	1791	1441	
		50					4575	4105	3625	3144	2664	2205	1758	1365	
4LR17.2X	Pf	30				16795	13743	11135	8897	7007	5410	4085	2988	2086	
		40				14796	12048	9690	7691	5997	4574	3400	2433	1651	
		50				12787	10342	8256	6486	4997	3759	2738	1912	1249	
	Pa	30				3532	3393	3190	2944	2655	2355	2034	1723	1434	
		40				4260	3982	3650	3286	2901	2515	2130	1755	1413	
		50				4902	4485	4025	3554	3083	2612	2162	1723	1338	
4LR23.2X	Pf	30								8869	6785	5058	3627	2473	
		40								7470	5630	4108	2871	1870	
		50								6111	4506	3198	2146	1318	
	Pa	30									3372	2943	2514	2085	1676
		40									3638	3096	2555	2044	1574
		50									3781	3137	2514	1931	1400
5LR23.2X	Pf	30				21657	17630	14204	11296	8825	6751	5033	3609	2461	
		40				18942	15322	12242	9629	7432	5602	4087	2857	1861	
		50				16227	13024	10300	8002	6080	4484	3182	2135	1312	
	Pa	30				4508	4308	4027	3687	3306	2885	2464	2044	1643	
		40				5410	5019	4578	4087	3566	3035	2504	2004	1543	
		50				6161	5590	4979	4348	3707	3075	2464	1893	1372	
6MR27.2X	Pf	30						17078	13597	10658	8191	6133	4444	3072	
		40						14764	11651	9030	6839	5037	3563	2375	
		50						12491	9747	7454	5549	3993	2734	1741	
	Pa	30							4894	4495	4044	3563	3061	2570	2099
		40							5560	4986	4382	3768	3153	2560	2017
		50							6082	5345	4597	3860	3143	2467	1863
7MR27.2X	Pf	30				25775	21037	16993	13529	10605	8150	6102	4421	3056	
		40				22617	18348	14691	11594	8985	6805	5012	3545	2364	
		50				19448	15658	12429	9699	7417	5522	3973	2720	1732	
	Pa	30				5340	5109	4798	4407	3965	3493	3001	2519	2058	
		40				6404	5962	5451	4888	4296	3694	3092	2509	1977	
		50				7297	6655	5962	5240	4507	3784	3082	2419	1827	
7MR32.2X	Pf	30								13068	10097	7624	5596	3933	
		40								11172	8536	6356	4582	3143	
		50								9337	7036	5150	3629	2423	
	Pa	30									4927	4369	3792	3214	2666
		40									5383	4674	3954	3275	2646
		50									5708	4856	4025	3254	2555
9MR32.2X	Pf	30				30461	24909	20144	16095	12666	9787	7389	5424	3813	
		40				26826	21814	17510	13884	10829	8274	6161	4441	3046	
		50				23141	18699	14926	11733	9050	6819	4992	3518	2348	
	Pa	30				6235	5993	5644	5209	4705	4173	3621	3069	2546	
		40				7494	7010	6438	5809	5141	4463	3776	3127	2527	
		50				8578	7862	7087	6283	5451	4638	3844	3108	2440	
6GR31.3X	Pf	30								12693	9808	7405	5436	3821	
		40								10851	8291	6174	4451	3053	
		50								9069	6834	5002	3525	2353	
	Pa	30									4786	4244	3683	3122	2590
		40									5229	4539	3840	3181	2570
		50									5544	4717	3909	3161	2481
8GR31.3X	Pf	30				28509	23313	18853	15064	11854	9160	6916	5076	3568	
		40				25106	20416	16388	12995	10134	7743	5766	4157	2851	
		50				21658	17501	13969	10981	8470	6382	4672	3292	2198	
	Pa	30				5923	5693	5362	4948	4469	3964	3439	2915	2419	
		40				7118	6658	6116	5518	4883	4240	3587	2970	2400	
		50				8148	7468	6732	5968	5178	4405	3651	2952	2318	
8GR39.3X	Pf	30								15625	11971	8930	6423		
		40								13186	9950	7239	5004		
		50								10796	7948	5578			
	Pa	30									5743	5053	4314	3556	
		40									6229	5325	4402	3479	
		50									6520	5422	4324		

PRISMACOM WATT (50 Hz) R407F

Condiciones de Cálculo: Gas de aspiración 25°C, sin subenfriamiento de líquido.
 Condizioni di calcolo: Gas di aspirazione 25°C senza sottoraffreddamento del liquido
 Conditions de Calcul: Gaz aspirés 25°C, sans sous-refroidissement du liquide
 Kälteleistung: 25°C Sauggasttemperatur ohne Flüssigkeitsunterkühlung
 Rating conditions: Suction return gas 25°C, without liquid subcooling.



COMPRESOR / COMPRESSOR	TEMP. CONDENSACION / CONDENSING TEMP. (°C)		TEMPERATURA DE EVAPORACION / EVAPORATING TEMPERATURE (°C)											
			H = Alta / High					M = Media / Medium			L = Baja / Low			
			12,5	10	7	5	0	-5	-10	-15	-20	-25	-30	-35
10GR39.3X	Pf	30	37998					30988	24945	19869	15547	11912	8885	6391
		40	32922					26782	21464	16959	13120	9901	7203	4979
		50	27942					22625	18022	14087	10742	7909	5550	
	Pa	30	7603					7322	6905	6362	5731	5043	4306	3549
		40	9145					8563	7865	7079	6216	5314	4393	3472
		50	10454					9581	8621	7593	6507	5411	4315	
10GR50.3X	Pf	30									18407	13961	10259	7204
		40									15288	11383	8158	5517
		50									12243	8890	6153	
	Pa	30									6631	5782	4912	4031
		40									7044	5962	4891	3840
		50									7214	5930	4668	
15GR50.3X	Pf	30	45603					37105	29769	23593	18315	13892	10208	7168
		40	39480					31880	25388	19856	15212	11327	8118	5489
		50	33252					26602	20975	16193	12182	8846	6123	
	Pa	30	9127					8693	8110	7411	6617	5770	4902	4023
		40	10757					9974	9074	8079	7030	5950	4881	3833
		50	12070					10958	9751	8491	7200	5919	4659	
12GR60.3X	Pf	30									24503	18751	13949	9958
		40									20835	15699	11415	7884
		50									17137	12677	8970	
	Pa	30									8784	7747	6691	5644
		40									9517	8226	6935	5673
		50									10036	8510	7004	
18GR60.3X	Pf	30	59468					48519	39126	31145	24381	18658	13879	9908
		40	51974					42241	33919	26766	20731	15621	11358	7845
		50	44333					35817	28566	22337	17052	12614	8925	
	Pa	30	11910					11334	10592	9723	8766	7732	6677	5633
		40	13999					13042	11949	10758	9498	8210	6921	5662
		50	15717					14419	13013	11539	10016	8493	6990	

COMPRESORES 4 CILINDROS EN V / 4 CYLINDERS IN V COMPRESSORS

5VLR26.4X	Pf	30						16472	13114	10280	7900	5915	4286	2963	
		40						14240	11238	8710	6597	4859	3437	2291	
		50						12048	9401	7189	5352	3851	2637	1679	
	Pa	30						4720	4335	3901	3437	2953	2479	2024	
		40						5362	4809	4227	3634	3042	2469	1945	
		50						5866	5155	4434	3723	3032	2380	1797	
7VLR26.4X	Pf	30	24860					20291	16390	13049	10229	7861	5886	4265	2948
		40	21814					17697	14169	11182	8667	6564	4835	3420	2280
		50	18758					15103	11988	9355	7153	5326	3832	2624	1670
	Pa	30	5151					4928	4628	4250	3824	3369	2895	2430	1985
		40	6177					5751	5257	4715	4144	3563	2982	2420	1907
		50	7039					6419	5751	5054	4347	3650	2972	2333	1762
5VLR29.4X	Pf	30						18759	14989	11795	9114	6881	5051	3550	
		40						16307	12930	10084	7705	5737	4136	2837	
		50						13900	10926	8428	6351	4649	3276	2187	
	Pa	30						5351	4938	4461	3956	3433	2909	2414	
		40						6103	5507	4874	4231	3579	2965	2395	
		50						6718	5957	5167	4396	3644	2946	2313	
7VLR29.4X	Pf	30	30526					24962	20186	16129	12693	9808	7405	5436	3821
		40	26882					21860	17547	13914	10851	8291	6174	4451	3053
		50	23190					18739	14958	11757	9069	6834	5002	3525	2353
	Pa	30	6341					6095	5741	5298	4786	4244	3683	3122	2590
		40	7622					7129	6548	5908	5229	4539	3840	3181	2570
		50	8724					7996	7208	6391	5544	4717	3909	3161	2481
7VLR33.4X	Pf	30						25946	20855	16556	12895	9830	7275	5170	
		40						22323	17859	14030	10799	8068	5796	3926	
		50						18759	14872	11553	8724	6344	4357		
	Pa	30						6119	5757	5297	4758	4161	3535	2888	
		40						7128	6531	5845	5111	4337	3544	2761	
		50						7931	7098	6207	5287	4337	3407		
10VLR33.4X	Pf	30	31711					25817	20751	16474	12830	9781	7238	5144	
		40	27424					22212	17770	13961	10746	8028	5767	3907	
		50	23186					18666	14798	11496	8680	6313	4335		
	Pa	30	6361					6107	5746	5286	4749	4153	3527	2883	
		40	7622					7114	6517	5833	5101	4329	3537	2756	
		50	8667					7915	7084	6195	5277	4329	3400		
7VLR38.4X	Pf	30						24583	19580	15321	11739	8756	6298		
		40						21153	16712	12930	9757	7099	4907		
		50						17761	13883	10586	7794	5469			
	Pa	30						6784	6251	5631	4955	4231	3487		
		40						7727	6956	6108	5221	4316	3411		
		50						8471	7461	6393	5317	4240			
10VLR38.4X	Pf	30	37260					30386	24460	19483	15245	11680	8713	6267	
		40	32282					26262	21047	16629	12865	9708	7063	4883	
		50	27400					22185	17672	13814	10533	7755	5442		
	Pa	30	7455					7179	6771	6238	5620	4945	4222	3480	
		40	8967					8397	7712	6942	6095	5211	4308	3404	
		50	10251					9395	8454	7446	6381	5306	4232		

PRISMACOM WATT (50 Hz) R407F

Condiciones de Cálculo: Gas de aspiración 25°C, sin subenfriamiento de líquido.
 Condizioni di calcolo: Gas di aspirazione 25°C senza sottoraffreddamento del liquido
 Conditions de Calcul: Gaz aspire 25°C, sans sous-refroidissement du liquide
 Kälteleistung: 25°C Sauggasttemperatur ohne Flüssigkeitsunterkühlung
 Rating conditions: Suction return gas 25°C, without liquid subcooling.



COMPRESOR / COMPRESSOR	TEMP. CONDENSACION / CONDENSING TEMP. (°C)		TEMPERATURA DE EVAPORACION / EVAPORATING TEMPERATURE (°C)												
			H = Alta / High					M = Media / Medium			L = Baja / Low				
			12,5	10	7	5	0	-5	-10	-15	-20	-25	-30	-35	-40
15VR73.4X	Pf	30									29379	22615	16956	12265	
		40									25182	19138	14092	9925	
		50									20936	15692	11317		
	Pa	30									10537	9342	8108	6903	
		40									11554	10043	8542	7091	
		50									12344	10557	8819		
25VR73.4X	Pf	30	70356					57483	46576	37192	29233	22502	16872	12204	
		40	61709					50310	40533	32132	25057	19043	14022	9875	
		50	52865					42941	34392	27022	20832	15614	11261		
	Pa	30	14222					13542	12674	11649	10516	9323	8091	6889	
		40	16853					15710	14419	13009	11531	10023	8525	7076	
		50	19090					17533	15858	14103	12320	10536	8801		
20VR83.4X	Pf	30									33991	26312	19857	14467	
		40									29345	22449	16678	11894	
		50									24601	18605	13587		
	Pa	30									12266	10887	9488	8119	
		40									13557	11826	10114	8481	
		50									14643	12599	10623		
30VR83.4X	Pf	30	80589					66086	53531	42873	33822	26182	19758	14395	
		40	70953					58008	46815	37277	29199	22337	16595	11835	
		50	61025					49735	39905	31583	24478	18512	13519		
	Pa	30	16498					15717	14721	13540	12242	10865	9469	8103	
		40	19729					18392	16879	15239	13530	11802	10094	8464	
		50	22570					20715	18743	16693	14614	12574	10602		
25VR93.4X	Pf	30									37827	29259	22058	16097	
		40									32586	24930	18504	13217	
		50									27345	20646	15076		
	Pa	30									13518	12023	10510	9006	
		40									14894	13025	11175	9398	
		50									16033	13846	11713		
35VR93.4X	Pf	30	89699					73555	59588	47707	37639	29114	21949	16017	
		40	78997					64486	52060	41449	32424	24806	18411	13151	
		50	67841					55234	44351	35100	27209	20543	15001		
	Pa	30	18048					17220	16147	14882	13491	11999	10489	8988	
		40	21414					20013	18421	16684	14864	12999	11153	9379	
		50	24307					22406	20350	18203	16001	13818	11689		
30VR118.4X	Pf	30									49294	38026	28579	20811	
		40									42341	32271	23880	16936	
		50									35292	26517	19229		
	Pa	30									17771	15719	13647	11614	
		40									19545	16965	14433	12017	
		50									20945	17905	14990		
40VR118.4X	Pf	30	117947					96476	78058	62409	49049	37836	28437	20707	
		40	103537					84357	68039	54011	42131	32111	23761	16852	
		50	88555					71951	57637	45423	35117	26385	19133		
	Pa	30	24110					22933	21430	19669	17735	15687	13620	11591	
		40	28752					26751	24493	22052	19506	16931	14405	11993	
		50	32753					29986	27039	23985	20903	17869	14960		